

# ONYXLITE®

## LED BULB

- Using advanced constant isolated current driver
- No UV and IR radiation release, mercury free
- Durable life span, more than 50,000 hours
- Energy-saving and environmental friendly
- No flickering and noise

**5 years**  
warranty  
**FREE**  
Maintenance  
Service



### APPLICATIONS



House



Hotel



Office



Exhibition Hall



Decorative

\* G24 to E27 Adapter available

### SPECIFICATIONS

LED LIGHT SOURCE	SMD 5730 Ultra Bright
LED LIFE CYCLE ( Hrs )	50 000 Hrs
HOUSING MATERIAL	Heat Sink Aluminium Alloy
PROTECTIVE GLASS	PC Cover
LAMP HOLDER	E27 / 26 & B22 Base
INPUT VOLTAGE ( Vac )	AC 85-265V
INPUT CURRENT ( mA )	290 mA
OUTPUT POWER ( W )	RATED POWER $\pm$ 0.5W
FREQUENCY ( Hz )	50 / 60 Hz
POWER FACTOR ( pf )	> 0.9
POWER EFFICIENCY ( % )	> 85%
LIGHT EFFICIENCY ( lm/w )	110 lm/w $\pm$ 5%
BEAM ANGLE( ° )	180°

COLOR RENDERING INDEX ( Ra )	75 - 85
COLOR TEMPERATURE ( K )	2700K-3300K (WW) 4000K-4500K (PW) 5500K-6500K (CW)
OPERATING TEMPERATURE ( °C )	-20 ~ 55°C
STORAGE TEMPERATURE ( °C )	-30 ~ 65°C
STORAGE HUMIDITY ( % R.H )	10% ~ 85%
INGRESS PROTECTION ( IP )	IP 66
WARRANTY	5 Years

#### COMPLIANCE STANDARD

CE, RoHS  
LVD Directive 2006/95/EC  
EMC Directive 2004/108/EC  
RoHS Directive 2011/65/EU



\* Customizable for dimming

#### POWER AVAILABLE

POWER	LED QTY (pcs)	LUMINOUS FLUX (lm)	DIMENSION (mm)	NET WEIGHT (kg)
3W	6	>310	Ø50*H90	0.35
5W	10	>520	Ø55*H102	0.41
7W	14	>720	Ø60*H124	0.43
9W	18	>930	Ø80*H135	0.71
12W	24	>1240	Ø80*H135	0.71
15W	24	>1560	Ø80*H135	0.71