

ONYXLITE®

UFO LED HIGH BAY LIGHT

- Using advanced constant isolated current driver
- No UV and IR radiation release, mercury free
- Durable life span, more than 50,000 hours
- Energy-saving and environmental friendly
- No flickering and noise
- Start instantly without time to preheat
- Perfect industrial design: excellent radiation combines with a beautiful appearance

5 years warranty
FREE Maintenance Service



APPLICATIONS



Shopping Mall



Warehouse



Factory



Sports Hall



Industrial Plant

SPECIFICATIONS

LED LIGHT SOURCE	Ultra Bright 3030 SMD LED
LED LIFE CYCLE (Hrs)	50 000 Hrs
HOUSING MATERIAL	Die-cast Heat Sink Aluminium Alloy
PROTECTIVE GLASS	PC Cover
INPUT VOLTAGE (Vac)	AC 85-305V
OUTPUT POWER (W)	RATED POWER $\pm 0.2W$
FREQUENCY (Hz)	50 / 60 Hz
POWER FACTOR (pf)	> 0.9
POWER EFFICIENCY (%)	> 85%
LIGHT EFFICIENCY (lm/w)	120 lm/w $\pm 10%$
BEAM ANGLE(°)	120°
INSTALLATION METHOD	Rotatable Holder , E 40 Base, Ring or Hook type

* Customizable for dimming

COLOR RENDERING INDEX (Ra)	75 - 85
COLOR TEMPERATURE (K)	2700K-3300K (WW) 4000K-4500K (PW) 5500K-6500K (CW)
OPERATING TEMPERATURE (°C)	-20 ~ 55°C
STORAGE TEMPERATURE (°C)	-40 ~ 85°C
STORAGE HUMIDITY (% R.H)	5% ~ 95%
INGRESS PROTECTION (IP)	IP 66
WARRANTY	5 Years

COMPLIANCE STANDARD

CE, RoHS
LVD Directive 2006/95/EC
EMC Directive 2004/108/EC
RoHS Directive 2011/65/EU



POWER AVAILABLE

POWER	INPUT CURRENT (A)	LUMINOUS FLUX (lm)	DIMENSION (mm)	NET WEIGHT (kg)
100W	2.1A	>11000	Ø385 x 170	5.00
150W	3.2A	>16500	Ø385 x 170	5.00
240W	5.1A	>26400	Ø385 x 170	5.00